Product datasheet

MUN LIGHT

Worktitude for light

ML1480SF25830NW



MUN LIGHT SUR Ø480 2500 WW WH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø480, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016

Weight: 4.534 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 2.311 lm
 °K:
 3000

 Plum:
 23,2W
 CRI:
 80

 Efficacy:
 99,6 lm/w
 MacAdam:
 <3</td>

Type: LOW POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 20W

Light output tolerance +/- 10%



















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU














MUN LIGHT




ML1480SF25830NW

MUN LIGHT SUR Ø480 2500 WW WH.

PHOTOMETRIC DATA:





alpha = 114,5°	H (m)	D (m)	Emax	Emed
	1	3,11	790	227
	2	6,22	198	57
	3	9,33	88	25
	4	12,44	49	14