Product datasheet

MUN LIGHT

ML1480SF25840NW





MUN LIGHT SUR Ø480 2500 NW WH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø480, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with 4000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016 Weight: 4.534 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	2.311 lm	٥K :	4000		
Plum:	23,2W	CRI :	80		
Efficacy:	99,6 lm/w	MacAdam:	<3		
Туре:	LOW POWER LED	Power Supply:	220-240V 50/60Hz		
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic		
Power:	20W				

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Worktitude for light

MUN LIGHT

ML1480SF25840NW

MUN LIGHT SUR Ø480 2500 NW WH.



10540010	180°	alpha = 114,5°	H (m)	D (m)	Emax	Emed
η = 100% Imax = 342 cd/klm			1	3,11	790	227
UTE: 1,00E + 0,00T	90° 90°		2	6,22	198	57
CIE: 46 78 96 100 100			3	9,33	88	25
	0.		4	12,44	49	14

