Product datasheet

MUN LIGHT

Worktitude for light

ML1480SF40830NB



MUN LIGHT SUR Ø480 4000 WW GRH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø480, LAMP brand. Made of textured graphite painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte graphite RAL 7021

Weight: 4.534 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 4.317 lm
 °K:
 3000

 Plum:
 61,9W
 CRI:
 80

 Efficacy:
 69,7 lm/w
 MacAdam:
 <3</td>

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 59W

Light output tolerance +/- 10%

















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU














MUN LIGHT




ML1480SF40830NB

MUN LIGHT SUR Ø480 4000 WW GRH.

PHOTOMETRIC DATA:





| alpha = 114,4° | H (m) | D (m) | Emax | Emed |
|----------------|-------|-------|------|------|
| | 1 | 3,10 | 1484 | 428 |
| | 2 | 6,21 | 371 | 107 |
| | 3 | 9,31 | 165 | 48 |
| | 4 | 12,41 | 93 | 27 |

Data according to regulations 2019/2020/EU and 2019/2015/EU