Product datasheet

MUN LIGHT

Worktitude for light

ML1480SF40830NW



MUN LIGHT SUR Ø480 4000 WW WH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø480, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016

Weight: 4.534 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 4.576 lm
 °K:
 3000

 Plum:
 61,9W
 CRI:
 80

 Efficacy:
 73,9 lm/w
 MacAdam:
 <3</td>

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 59W

Light output tolerance +/- 10%



CLASE

IK 08 IP 20 **LED** 3000°K

PMMA diffuser







CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU














MUN LIGHT




ML1480SF40830NW

MUN LIGHT SUR Ø480 4000 WW WH.

PHOTOMETRIC DATA:





alpha = 114,4°	H (m)	D (m)	Emax	Emed
	1	3,10	1573	453
	2	6,21	393	113
	3	9,31	175	50
	4	12,41	98	28