Product datasheet

MUN LIGHT

ML1480SF40840NB



MUN LIGHT SUR Ø480 4000 NW GRH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø480, LAMP brand. Made of textured graphite painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 4000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte graphite RAL 7021 Weight: 4.534 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	4.317 lm	٥K :	4000		
Plum:	61,9W	CRI :	80		
Efficacy:	69,7 lm/w	MacAdam:	<3		
Туре:	MID POWER LED	Power Supply:	220-240V 50/60Hz		
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)	Gear:	Electronic		
Power:	59W				

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light

MUN LIGHT

ML1480SF40840NB

MUN LIGHT SUR Ø480 4000 NW GRH.



PHOTOMETRIC DATA :

10540032	180°	alpha = 114,4°	H (m)	D (m)	Emax	Emed
η = 100% Imax = 344 cd/klm			1	3,10	1484	428
UTE: 1,00E + 0,00T	90° 90°		2	6,21	371	107
CIE: 47 79 96 100 100			3	9,31	165	48
				0,01	100	
	0°		4	12,41	93	27