Product datasheet

MUN LIGHT

ML1480SF40840NW





MUN LIGHT SUR Ø480 4000 NW WH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø480, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 4000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	4.576 lm	٥K :	4000	
Plum:	61,9W	CRI :	80	
Efficacy:	73,9 lm/w	MacAdam:	<3	
Туре:	MID POWER LED	Power Supply:	220-240V 50/60Hz	
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)	Gear:	Electronic	
Power:	59W			

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



Worktitude for light

MUN LIGHT

ML1480SF40840NW

MUN LIGHT SUR Ø480 4000 NW WH.



10540030	180°	alpha = 114,4°	H (m)	D (m)	Emax	Emed
η = 100% Imax = 344 cd/klm			1	3,10	1573	453
UTE: 1,00E + 0,00T	90° 90°		2	6,21	393	113
CIE: 47 79 96 100 100			3	9,31	175	50
	0°		4	12,41	98	28

Worktitude for light