Product datasheet

MUN LIGHT

Worktitude for light


ML1480SU40830NB



MUN LIGHT SUS Ø480 4000 WW GRH.

Description:

Round suspended downlight model MUN LIGHT SUS Ø480, LAMP brand. Made of textured graphite painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte graphite RAL 7021

Weight: 4.716 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 4.317 lm
 °K:
 3000

 Plum:
 61,9W
 CRI:
 80

 Efficacy:
 69,7 lm/w
 MacAdam:
 <3</td>

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 59W

Light output tolerance +/- 10%



















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU














MUN LIGHT




ML1480SU40830NB

MUN LIGHT SUS Ø480 4000 WW GRH.

PHOTOMETRIC DATA:





alpha = 114,4°	H (m)	D (m)	Emax	Emed
	1	3,10	1484	428
	2	6,21	371	107
	3	9,31	165	48
	4	12,41	93	27