#### **Product datasheet**

#### **MUN LIGHT**


#### ML1480SU40830NW



#### MUN LIGHT SUS Ø480 4000 WW WH.

#### Description:

Round suspended downlight model MUN LIGHT SUS Ø480, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 pro tection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016

Weight: 4.716 g

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 4.576 lm °K: 3000 Plum: 61,9W CRI: 80 Efficacy: 73,9 lm/w MacAdam: <3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

59W Power:

### Light output tolerance +/- 10%























**CUSTOM MADE OPTIONS:** 









Data according to regulations 2019/2020/EU and 2019/2015/EU














# **MUN LIGHT**




ML1480SU40830NW

## MUN LIGHT SUS Ø480 4000 WW WH.

### **PHOTOMETRIC DATA:**





alpha = 114,4°	H (m)	D (m)	Emax	Emed
	1	3,10	1573	453
	2	6,21	393	113
	3	9,31	175	50
	4	12,41	98	28