#### **Product datasheet**

#### **MUN LIGHT**

# Worktitude for light

#### ML1480SU40840NW



## MUN LIGHT SUS Ø480 4000 NW WH.

#### Description:

Round suspended downlight model MUN LIGHT SUS Ø480, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 4000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016

Weight: 4.716 g

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

 Light output:
 4.576 lm
 °K:
 4000

 Plum:
 61,9W
 CRI:
 80

 Efficacy:
 73,9 lm/w
 MacAdam:
 <3</td>

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 59W

#### Light output tolerance +/- 10%



















## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU














## **MUN LIGHT**




ML1480SU40840NW

## MUN LIGHT SUS Ø480 4000 NW WH.

#### **PHOTOMETRIC DATA:**





| alpha = 114,4° | H (m) | D (m) | Emax | Emed |
|----------------|-------|-------|------|------|
|                | 1     | 3,10  | 1573 | 453  |
|                | 2     | 6,21  | 393  | 113  |
|                | 3     | 9,31  | 175  | 50   |
|                | 4     | 12,41 | 98   | 28   |