#### **Product datasheet**

### **MUN LIGHT**

### ML1780SF65840NW



## MUN LIGHT SUR Ø780 6700 NW WH.

### Description:

Round for ceiling mounting downlight model MUN LIGHT SUR  $\emptyset$ 780, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with 4000K color temperature, CRI 80 and control gear incl uded. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016

Weight: 9.526 g

Installation: Surface

### **TECHNICAL SPECIFICATIONS:**

Light output: 6.994 Im °K: 4000 Plum: 63,6W CRI: 80 Efficacy: 110 lm/w MacAdam: <3

Type: LOW POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

60W Power:

## Light output tolerance +/- 10%



CLASE

IK 80















## **CUSTOM MADE OPTIONS:**





















# **MUN LIGHT**








### **PHOTOMETRIC DATA:**





	(Fee			
alpha = 113,0°	H (m)	D (m)	Emax	Emed
	1	3,02	2447	726
	2	6,05	612	181
	3	9,07	272	81
	4	12,09	153	45