Product datasheet

MUN LIGHT

Worktitude for light


ML1780SU65830NB



MUN LIGHT SUS Ø780 6700 WW GRH.

Description:

Round suspended downlight model MUN LIGHT SUS Ø780, LAMP brand. Made of textured graphite painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte graphite RAL 7021

Weight: 10.864 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 6.602 lm
 °K:
 3000

 Plum:
 63,6W
 CRI:
 80

 Efficacy:
 103,8 lm/w
 MacAdam:
 <3</td>

Type: LOW POWER OSRAM Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) **Gear**:

Power: 60W

















CUSTOM MADE OPTIONS:





















Electronic


MUN LIGHT




ML1780SU65830NB

MUN LIGHT SUS Ø780 6700 WW GRH.

PHOTOMETRIC DATA:





alpha = 113,0°	H (m)	D (m)	Emax	Emed
	1	3,02	2310	685
	2	6,05	578	171
	3	9,07	257	76
	4	12,09	144	43