Product datasheet

MUN LIGHT




ML1780SU65830NW



MUN LIGHT SUS Ø780 6700 WW WH.

Description:

Round suspended downlight model MUN LIGHT SUS Ø780, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 pro tection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016

Weight: 10.864 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 6.994 lm
 °K:
 3000

 Plum:
 63,6W
 CRI:
 80

 Efficacy:
 110 lm/w
 MacAdam:
 <3</td>

Type: LOW POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 60W

Light output tolerance +/- 10%



CLASE

IK 08













CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU














MUN LIGHT




ML1780SU65830NW

MUN LIGHT SUS Ø780 6700 WW WH.

PHOTOMETRIC DATA:





alpha = 113,0°	H (m)	D (m)	Emax	Emed
	1	3,02	2447	726
	2	6,05	612	181
	3	9,07	272	81
	4	12,09	153	45