#### **Product datasheet**

#### **MUN LIGHT**


#### ML1780SU65840NW



# MUN LIGHT SUS Ø780 6700 NW WH.

#### Description:

Round suspended downlight model MUN LIGHT SUS Ø780, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with 4000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016

Weight: 10.864 g

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 6.994 Im °K: 4000 Plum: 63,6W CRI: 80 Efficacy: 110 lm/w MacAdam: <3

Type: LOW POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

60W Power:

### Light output tolerance +/- 10%





















# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU















# **MUN LIGHT**








### **PHOTOMETRIC DATA:**





| alpha = 113,0° | H (m) | D (m) | Emax | Emed |
|----------------|-------|-------|------|------|
|                | 1     | 3,02  | 2447 | 726  |
|                | 2     | 6,05  | 612  | 181  |
|                | 3     | 9,07  | 272  | 81   |
|                | 4     | 12,09 | 153  | 45   |