


ML2SF35LOPR940NW



MUN LIGHT G2 SF Ø350 LO PRISM 9NW NR WH

Description:


LAMP suspended or surface mounted luminaire MUN LIGHT G2 SF Ø350 LO PRISM. Manufactured from recycled aluminium extrusion with a 95% recycling rate, with a PRISMATIC polycarbonate diffuser to control light distribution and reduce glare UGR <19. Model for LED MID-POWER, colour temperature 4000K and CRI90. Electronic ON OFF gear included. IP20, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L80 B10. Available finishes: White and black.

Finish: Texturised matt white

Weight: 1.600 g

Installation: Surface
TECHNICAL SPECIFICATIONS:


Light output:	1.491 lm	°K :	4000
Plum:	18,5W	CRI :	90
Efficacy:	124,3 lm/w	R9 :	55
UGR:	<19	MacAdam:	3
Type:	MID POWER	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	9,5W		

Light output tolerance +/- 10%
**CUSTOM MADE OPTIONS:**

ML2SF35LOPR940NW

MUN LIGHT G2 SF Ø350 LO PRISM 9NW NR WH

PHOTOMETRIC DATA :



MUN LIGHT

ACCESORIES :

Suspension



Product code:

ML2SUEMSF1500NW

ML2SUEMSF3000NW

Description:

MUN LIGHT G2 ACC SUSP ELMEC 1500MM N W

MUN LIGHT G2 ACC SUSP ELMEC 3000MM N W