


MUN LIGHT

ML2SF35MOPR930NB



MUN LIGHT G2 SF Ø350 MO PRISM 9WW NR BK

Description:

LAMP suspended or surface mounted luminaire MUN LIGHT G2 SF Ø350 MO PRISM. Manufactured from recycled aluminium extrusion with a 95% recycling rate, with a PRISMATIC polycarbonate diffuser to control light distribution and reduce glare UGR <19. Model for LED MID-POWER, colour temperature 3000K and CRI90. Electronic ON OFF gear included. IP20, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L80 B10. Available finishes: White and black.

Finish: Texturised matte graphite RAL 7021

Weight: 1.600 g

Installation: Surface

TECHNICAL SPECIFICATIONS:


Light output:	2.003 lm	°K :	3000
Plum:	18,5W	CRI :	90
Efficacy:	108,3 lm/w	R9 :	51
UGR:	<19	MacAdam:	3
Type:	MID POWER	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	16,6W		

Light output tolerance +/- 10%


CUSTOM MADE OPTIONS:



PHOTOMETRIC DATA :



MUN LIGHT

ACCESORIES :

Suspension



Product code:

ML2SUEMSF1500NB

ML2SUEMSF3000NB

Description:

MUN LIGHT G2 ACC SUSP ELMEC 1500MM N B

MUN LIGHT G2 ACC SUSP ELMEC 3000MM N B