


MUN LIGHT

ML2SF45LOPR940DW



MUN LIGHT G2 SF Ø450 LO PRISM 9NW DA WH

Description:

LAMP suspended or surface mounted luminaire MUN LIGHT G2 SF Ø450 LO PRISM. Manufactured from recycled aluminium extrusion with a 95% recycling rate, with a PRISMATIC polycarbonate diffuser to control light distribution and reduce glare UGR <19. Model for LED MID-POWER, colour temperature 4000K and CRI90. Electronic DALI gear included. IP20, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L80 B10. Available finishes: White and black.


Finish: Texturised matt white

Weight: 2.730 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	2.020 lm	°K :	4000
Plum:	16,8W	CRI :	90
Efficacy:	120,2 lm/w	R9 :	55
UGR:	<19	MacAdam:	3
Type:	MID POWER	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI2
Power:	15,9W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



ML2SF45LOPR940DW

MUN LIGHT G2 SF Ø450 LO PRISM 9NW DA WH

PHOTOMETRIC DATA :



ACCESORIES :

Suspension



Product code:

ML2SUEMSF1500DW

ML2SUEMSF3000DW

Description:

MUN LIGHT G2 ACC SUSP ELMEC 1500MM D W

MUN LIGHT G2 ACC SUSP ELMEC 3000MM D W