Product datasheet

MINI SHOT LED




MN215MF840NG



SHOT 120 G2 1500 NW MFL GR.

Description:

Outdoor spotlight model SHOT 120 1500, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey



Finish: Texturised grey

Weight: 3.188 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.097 lm °K: 4000 Plum: 11,9W CRI: 80 Efficacy: 92,2 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

10W Power:

Light output tolerance +/- 10%

































CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU





















+34937366800


MINI SHOT LED





MN215MF840NG


SHOT 120 G2 1500 NW MFL GR.

PHOTOMETRIC DATA:









Product datasheet

MINI SHOT LED



ACCESORIES:

Optical



Product code:

Description:

MSSC134B

SHOT 120 ACC. ANTIGLARE SCREEN.