Product datasheet

MINI SHOT LED


MN230MF830NG



SHOT 120 G2 2900 WW MFL GR.

Description:

Outdoor spotlight model SHOT 120 2900, LAMP brand. Made of texturised gris lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 3000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey



Finish: Texturised grey

Weight: 3.212 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 2.155 lm °K: 3000 Plum: 23W CRI: 80 Efficacy: 93,7 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

20W Power:

Light output tolerance +/- 10%





























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU






















MINI SHOT LED




MN230MF830NG

SHOT 120 G2 2900 WW MFL GR.

PHOTOMETRIC DATA:





alpha = 23,8°	H (m)	D (m)	Emax	Emed
\wedge	1	0,42	10621	7449
	2	0,84	2655	1862
	3	1,26	1180	828
	4	1,68	664	466

Product datasheet

MINI SHOT LED



ACCESORIES:

Optical



Product code:

Description:

MSSC134B

SHOT 120 ACC. ANTIGLARE SCREEN.