Product datasheet

MINI SHOT LED


MN230MF840NG



SHOT 120 G2 2900 NW MFL GR.

Description:

Outdoor spotlight model SHOT 120 2900, LAMP brand. Made of texturised gris lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey



Finish: Texturised grey

Weight: 3.212 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 2.155 lm °K: 4000 Plum: 23W CRI: 80 Efficacy: 93,7 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

20W Power:

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU





















+34937366800


MINI SHOT LED




MN230MF840NG

SHOT 120 G2 2900 NW MFL GR.

PHOTOMETRIC DATA:





| alpha = 23,8° | H (m) | D (m) | Emax | Emed |
|---------------|-------|-------|-------|------|
| \wedge | 1 | 0,42 | 10621 | 7449 |
| | 2 | 0,84 | 2655 | 1862 |
| | 3 | 1,26 | 1180 | 828 |
| | 4 | 1,68 | 664 | 466 |

Product datasheet

MINI SHOT LED



ACCESORIES:

Optical



Product code:

Description:

MSSC134B

SHOT 120 ACC. ANTIGLARE SCREEN.