### **Product datasheet**

## **MINI SHOT LED**




## MN230SP840NA



## SHOT 120 G2 2900 NW SP ANT.

## Description:

Outdoor spotlight model SHOT 120 2900, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Spot optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey



Finish: Textured anthracite

Weight: 3.212 g

Installation: Surface

## **TECHNICAL SPECIFICATIONS:**

Light output: 2.215 lm °K: 4000 Plum: 23W CRI: 80 Efficacy: 96,3 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

20W Power:

## Light output tolerance +/- 10%



























# **CUSTOM MADE OPTIONS:**





























# **MINI SHOT LED**





MN230SP840NA

## SHOT 120 G2 2900 NW SP ANT.

## PHOTOMETRIC DATA:

MN230SP840NA  $\eta$  = 99% Imax = 14950 cd/klm UTE:





alpha = 11,4°	H (m)	D (m)	Emax	Emed
$\bigwedge$	1	0,20	32881	21894
	2	0,40	8220	5473
	3	0,60	3653	2433
	4	0,80	2055	1368

## **Product datasheet**

# **MINI SHOT LED**



ACCESORIES:

Optical



Product code:

Description:

MSSC134B SHOT 120 ACC. ANTIGLARE SCREEN.