#### **Product datasheet**

#### **MINI SHOT LED**


#### MN230SP840NG



#### SHOT 120 G2 2900 NW SP GR.

#### Description:

Outdoor spotlight model SHOT 120 2900, LAMP brand. Made of texturised gris lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Spot optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey



Finish: Texturised grey

Weight: 3.212 g

Installation: Surface

#### **TECHNICAL SPECIFICATIONS:**

Light output: 2.215 lm °K: 4000 Plum: 23W CRI: 80 Efficacy: 96,3 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

20W Power:

#### Light output tolerance +/- 10%





























# **CUSTOM MADE OPTIONS:**





























## **MINI SHOT LED**




MN230SP840NG

## SHOT 120 G2 2900 NW SP GR.

## PHOTOMETRIC DATA:

MN230SP840NG  $\eta$  = 99% Imax = 14950 cd/klm UTE:



alpha = 11,4°	H (m)	D (m)	Emax	Emed
	1	0,20	32881	21894
	2	0,40	8220	5473
	3	0,60	3653	2433
	4	0,80	2055	1368

## **Product datasheet**

## **MINI SHOT LED**



ACCESORIES:

Optical



Product code:

Description:

MSSC134B

SHOT 120 ACC. ANTIGLARE SCREEN.