Product datasheet

MINI SHOT LED


MN240MF830NG



SHOT 120 G2 3800 WW MFL GR.

Description:

Outdoor spotlight model SHOT 120 3800, LAMP brand. Made of texturised gris lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 3000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey



Finish: Texturised grey

Weight: 3.212 g

Maximum surface exposed to wind: 0.12 M2

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 2.937 Im °K: 3000 Plum: 33,5W CRI: 80 Efficacy: 87,7 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

30W Power:

Light output tolerance +/- 10%







































CUSTOM MADE OPTIONS:





























Data according to regulations 2019/2020/EU and 2019/2015/EU

MINI SHOT LED




MN240MF830NG

SHOT 120 G2 3800 WW MFL GR.

PHOTOMETRIC DATA:

MN240MF830NG η = 100% Imax = 4976 cd/klm UTE: CIE: 98 100 100 100 100



alpha = 23,7°	H (m)	D (m)	Emax	Emed
\wedge	1	0,42	14557	10201
	2	0,84	3639	2550
	3	1,26	1617	1133
	4	1,68	910	638

Product datasheet

MINI SHOT LED



ACCESORIES:

Optical



Product code:

Description:

MSSC134B

SHOT 120 ACC. ANTIGLARE SCREEN.