# **Product datasheet**

# **MINI SHOT LED**


# MN2BJ30MF830NG



# SHOT 120 G2 BJ 2900 WW MFL GR.

# Description:

Outdoor spotlight model SHOT 120 2900 WW MFL, LAMP brand, for installation in columns of ø60-127. Made of texturised gris lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 3000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey.



Finish: Texturised grey

Weight: 2.816 g

Installation: Surface

# **TECHNICAL SPECIFICATIONS:**

Light output: 2.155 lm °K: 3000 Plum: 23W CRI: 80 Efficacy: 93,7 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

20W Power:

### Light output tolerance +/- 10%



























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU





















# **MINI SHOT LED**





MN2BJ30MF830NG


SHOT 120 G2 BJ 2900 WW MFL GR.

# **PHOTOMETRIC DATA:**

MN2BJ30MF830NG  $\eta$  = 100% Imax = 4947 cd/klm UTE: CIE: 98 100 100 100 100







# **Product datasheet**

# **MINI SHOT LED**



ACCESORIES:

Optical



Product code:

Description:

MSSC134B SHOT 120 ACC. ANTIGLARE SCREEN.