#### **Product datasheet**

#### **MINI SHOT LED**

# Worktitude for light


#### MN2BJ30SP830NG



#### **SHOT 120 G2 BJ 2900 WW SP GR**

#### Description:

Outdoor spotlight model SHOT 120 2900 WW SP, LAMP brand, for installation in columns of ø60-127. Made of texturised gris lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 3000K colour temperature, CRI 80 and control gear included. With Spot optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey.



Finish: Texturised grey

Weight: 2.816 g

Installation: Surface

#### **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.215 lm
 °K:
 3000

 Plum:
 23W
 CRI:
 80

 Efficacy:
 96,3 lm/w
 MacAdam:
 3

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 20W

#### Light output tolerance +/- 10%

























# \_ \_\_

# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU























## **MINI SHOT LED**





MN2BJ30SP830NG


SHOT 120 G2 BJ 2900 WW SP GR

#### **PHOTOMETRIC DATA:**

MN2BJ30SP830NG η = 99% Imax = 14950 cd/klm UTE: CIE: 103 100 100 100 99







Data according to regulations 2019/2020/EU and 2019/2015/EU

#### **Product datasheet**

## **MINI SHOT LED**



ACCESORIES:

Optical



Product code:

Description:

MSSC134B SHOT 120 ACC. ANTIGLARE SCREEN.