MINI SHOT LED


MN2BJ40MF840NA



SHOT 120 G2 BJ 3800 NW MFL ANT.

Description:

Outdoor spotlight model SHOT 120 3800 NW MFL, LAMP brand, for installation in columns of ø60-127. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey.



Finish: Textured anthracite

Weight: 2.816 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 2.937 lm °K: 4000 Plum: 33,5W CRI: 80 Efficacy: 87,7 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

30W Power:

Light output tolerance +/- 10%





































CUSTOM MADE OPTIONS:






























MINI SHOT LED





MN2BJ40MF840NA


SHOT 120 G2 BJ 3800 NW MFL ANT.

PHOTOMETRIC DATA:









Product datasheet

MINI SHOT LED



ACCESORIES:

Optical



Product code:

Description:

MSSC134B SHOT 120 ACC. ANTIGLARE SCREEN.