MINI SHOT LED

LAMP Worktitude for light


MN2BJ40SP830NG



SHOT 120 G2 BJ 3800 WW SP GR.

Description:

Outdoor spotlight model SHOT 120 3800 WW SP, LAMP brand, for installation in columns of ø60-127. Made of texturised gris lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 3000K colour temperature, CRI 80 and control gear included. With Spot optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey.



Finish: Texturised grey

Weight: 2.816 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 3.032 lm
 % :
 3000

 Plum:
 33,5W
 CRI :
 80

 Efficacy:
 90,5 lm/w
 MacAdam:
 3

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 30W

Light output tolerance +/- 10%























Group 0 En 62471

CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU





















MINI SHOT LED





MN2BJ40SP830NG


SHOT 120 G2 BJ 3800 WW SP GR.

PHOTOMETRIC DATA:

MN2BJ40SP830NG η = 99% Imax = 15011 cd/klm UTE: CIE: 103 100 100 100 99







Product datasheet

MINI SHOT LED



ACCESORIES:

Optical



Product code:

Description:

MSSC134B SHOT 120 ACC. ANTIGLARE SCREEN.