


## MINI SHOT LED

MN2BR30MF840NG



## SHOT 120 G2 BR 2900 NW MFL GR.

## Description:

Outdoor spotlight model SHOT 120 BR 2900, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey

Finish: Texturised grey

Weight: 2.816 g

Installation: Surface

## TECHNICAL SPECIFICATIONS:

Light output:	2.155 lm	°K :	4000
Plum:	23W	CRI :	80
Efficacy:	93,7 lm/w	MacAdam:	3
Type:	HIGH POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	60.000 L90 B10 (Ta=25°C)	Gear:	Electronic
Power:	20W		

Light output tolerance +/- 10%



## CUSTOM MADE OPTIONS:




ACCESORIES :

Assembly




**Product code:**  
MSFIC

**Description:**  
SHOT 120 ACC. FIXATION POLE BASE




**Product code:**  
MSFTSQG

**Description:**  
SHOT 120 ACC. FIXATION PATTERN.




**Product code:**  
MSPO1000A

**Description:**  
SHOT 120 ACC. 1M POLE ANT.




**Product code:**  
MSPO1000G

**Description:**  
SHOT 120 ACC. 1M POLE GR.



**Product code:**  
MSPO2500A

**Description:**  
SHOT 120 ACC. 2,5M POLE ANT.




**Product code:**  
MSPO2500G

**Description:**  
SHOT 120 ACC. 2,5M POLE GR.


ACCESORIES :

Support




**Product code:**  
MSAR1000A

**Description:**  
SHOT 120 ACC. WALL ARM ANT.



**Product code:**  
MSAR1000G

**Description:**  
SHOT 120 ACC. WALL ARM GR.



**Product code:**  
MSSPM

**Description:**  
SHOT 120 BRACKET ACC. SPIKE.

---

**ACCESORIES :**

**Optical**



**Product code:**

MSSC134B

**Description:**

SHOT 120 ACC. ANTIGLARE SCREEN.