


MINI SHOT LED

MN2BR40MF840NA



SHOT 120 G2 BR 3800 NW MFL ANT.

Description:

Outdoor spotlight model SHOT 120 BR 3800, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60.000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey

Finish: Textured anthracite

Weight: 2.816 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	2.937 lm	°K :	4000
Plum:	33,5W	CRI :	80
Efficacy:	87,7 lm/w	MacAdam:	3
Type:	HIGH POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	60.000 L90 B10 (Ta=25°C)	Gear:	Electronic
Power:	30W		

Light output tolerance +/- 10%




CUSTOM MADE OPTIONS:



MN2BR40MF840NA

SHOT 120 G2 BR 3800 NW MFL ANT.

PHOTOMETRIC DATA :




ACCESORIES :

Assembly




Product code:
MSFIC

Description:
SHOT 120 ACC. FIXATION POLE BASE




Product code:
MSFTSQG

Description:
SHOT 120 ACC. FIXATION PATTERN.




Product code:
MSPO1000A

Description:
SHOT 120 ACC. 1M POLE ANT.




Product code:
MSPO1000G

Description:
SHOT 120 ACC. 1M POLE GR.



Product code:
MSPO2500A

Description:
SHOT 120 ACC. 2,5M POLE ANT.




Product code:
MSPO2500G

Description:
SHOT 120 ACC. 2,5M POLE GR.


ACCESORIES :

Support




Product code:
MSAR1000A

Description:
SHOT 120 ACC. WALL ARM ANT.



Product code:
MSAR1000G

Description:
SHOT 120 ACC. WALL ARM GR.



Product code:
MSSPM

Description:
SHOT 120 BRACKET ACC. SPIKE.

ACCESORIES :

Optical



Product code:

MSSC134B

Description:

SHOT 120 ACC. ANTIGLARE SCREEN.