Product datasheet

MINI SHOT LED

Worktitude for light


MN2BR40MF840NG



SHOT 120 G2 BR 3800 NW MFL GR.

Description:

Outdoor spotlight model SHOT 120 BR 3800, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey



Finish: Texturised grey

Weight: 2.816 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 2.937 lm
 %K:
 4000

 Plum:
 33,5W
 CRI:
 80

 Efficacy:
 87,7 lm/w
 MacAdam:
 3

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 30W

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:





























MINI SHOT LED





MN2BR40MF840NG

SHOT 120 G2 BR 3800 NW MFL GR.

PHOTOMETRIC DATA:

MN2BR40MF840NG η = 100% Imax = 4976 cd/klm UTE:





alpha = 23,7°	H (m)	D (m)	Emax	Emed
\wedge	1	0,42	14557	10201
	2	0,84	3639	2550
	3	1,26	1617	1133
	4	1,68	910	638