
Product datasheet

MINI SHOT LED

MN2BR40SP830NA





SHOT 120 G2 BR 3800 WW SP ANT.

Description:

Outdoor spotlight model SHOT 120 BR 3800, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 3000K colour temperature, CRI 80 and control gear included. With Spot optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey

Finish: Textured anthracite


Weight: 2.816 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	3.032 lm	⁰К:	3000
Plum:	33,5W	CRI :	80
Efficacy:	90,5 lm/w	MacAdam:	3
Туре:	HIGH POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	60.000 L90 B10 (Ta=25°C)	Gear:	Electronic
Power:	30W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light

Product datasheet

MINI SHOT LED

MN2BR40SP830NA

SHOT 120 G2 BR 3800 WW SP ANT.



PHOTOMETRIC DATA :

MN2BR40SP830NA	180°	alpha = 11,4°	H (m)	D (m)	Emax	Emed
η = 99% Imax = 15011 cd/klm			1	0,20	45195	30094
UTE:	90° 90°		2	0,40	11299	7523
CIE: 103 100 100 100 99			3	0,60	5022	3344
			4	0,80	2825	1881
	0°		4	0,00	2025	1001