MINI SHOT LED


MN2BR40SP840NA



SHOT 120 G2 BR 3800 NW SP ANT.

Description:

Outdoor spotlight model SHOT 120 BR 3800, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Spot optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey



Finish: Textured anthracite

Weight: 2.816 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 3.032 lm °K: 4000 Plum: 33,5W CRI: 80 Efficacy: 90,5 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

30W Power:

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:





























Data according to regulations 2019/2020/EU and 2019/2015/EU

MINI SHOT LED




MN2BR40SP840NA

SHOT 120 G2 BR 3800 NW SP ANT.

PHOTOMETRIC DATA:

MN2BR40SP840NA $_{\eta}$ = 99% Imax = 15011 cd/klm UTE:





alpha = 11,4°	H (m)	D (m)	Emax	Emed
\bigwedge	1	0,20	45195	30094
	2	0,40	11299	7523
	3	0,60	5022	3344
	4	0,80	2825	1881