Product datasheet

MINI SHOT LED

Worktitude for light


MN2BR40SP840NG



SHOT 120 G2 BR 3800 NW SP GR.

Description:

Outdoor spotlight model SHOT 120 BR 3800, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Spot optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey



Finish: Texturised grey

Weight: 2.816 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 3.032 lm
 % :
 4000

 Plum:
 33,5W
 CRI :
 80

 Efficacy:
 90,5 lm/w
 MacAdam:
 3

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 30W

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU























MINI SHOT LED




MN2BR40SP840NG


SHOT 120 G2 BR 3800 NW SP GR.

PHOTOMETRIC DATA:

MN2BR40SP840NG η = 99% Imax = 15011 cd/klm UTE:

CIE: 103 100 100 100 99





alpha = 11,4°	H (m)	D (m)	Emax	Emed
\bigwedge	1	0,20	45195	30094
	2	0,40	11299	7523
	3	0,60	5022	3344
	4	0,80	2825	1881