Product datasheet

MOODY




MO2SU20FL830NBB



MOODY G2 SUS 2000 WW FL BK/BK.

Description:

Suspended downlight modeMOODY G2 SUS 2000 WW FL BK/BK. Lamp brand. Body made of black aluminium extrusion, with MFL polycarbonate reflector, and black trim ring, with high visual comfort (UGR <19).Model for COB LEDs with warm white colour temperature and built-in electronic equipment. With IP20 degree of protection. Insulation class I.



Finish: Matte black RAL 9011

Weight: 640 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 1.317 lm
 °K:
 3000

 Plum:
 20,5W
 CRI:
 80

 Efficacy:
 64,2 lm/w
 MacAdam:
 3

Type: COB PHILIPS Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 18W

















CUSTOM MADE OPTIONS:



























MOODY



MOODY G2 SUS 2000 WW FL BK/BK.



PHOTOMETRIC DATA:

MO2SU20FL830NBB η = 100% Imax = 2095 cd/klm UTE: CIE: 98 100 100 100 100

