#### **Product datasheet**

## **MOODY**

# Worktitude for light


## MO2SU20FL830NBW



## MOODY G2 SUS 2000 WW FL BK/WH.

## Description:

Suspended downlight modeMOODY G2 SUS 2000 WW FL BK/WH. Lamp brand. Body made of white aluminium extrusion, with MFL polycarbonate reflector, and black trim ring, with high visual comfort (UGR <19).Model for COB LEDs with warm white colour temperature and built-in electronic equipment. With IP20 degree of protection. Insulation class I.



Finish: Matte white RAL 9010

Weight: 640 g

Installation: Suspended

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 1.317 lm
 ⁰K :
 3000

 Plum:
 20,5W
 CRI :
 80

 Efficacy:
 64,2 lm/w
 MacAdam:
 3

**Type:** COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 18W

## Light output tolerance +/- 10%

















## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU



















## **MOODY**





## MOODY G2 SUS 2000 WW FL BK/WH.




## **PHOTOMETRIC DATA:**

MO2SU20FL830NBW
η = 100%
Imax = 2095 cd/klm
UTE:
CIE: 98 100 100 100 100







Data according to regulations 2019/2020/EU and 2019/2015/EU