Product datasheet

MOODY

Worktitude for light


MO2SU20MF830NBW



MOODY G2 SUS 2000 WW MFL BK/WH.

Description:

Suspended downlight modeMOODY G2 SUS 2000 WW MFL BK/WH. Lamp brand. Body made of white aluminium extrusion, with MFL polycarbonate reflector, and black trim ring, with high visual comfort (UGR <19). Model for COB LEDs with warm white colour temperature and built-in electronic equipment. With IP20 degree of protection. Insulation class I.



Finish: Matte white RAL 9010

Weight: 640 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 1.503 lm
 °K:
 3000

 Plum:
 20,5W
 CRI:
 80

 Efficacy:
 73,3 lm/w
 MacAdam:
 3

Type: COB PHILIPS Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 18W

















CUSTOM MADE OPTIONS:

























MOODY







PHOTOMETRIC DATA:

MO2SU20MF830NBW $_{\eta}$ = 100% $_{lmax}$ = 3143 cd/klm UTE: CIE: 99 100 100 100 100

