#### **Product datasheet**

## **MOODY**

# Worktitude for light


## MO2SU20MF840NBB



## MOODY G2 SUS 2000 NW MFL BK/BK.

## Description:

Suspended downlight modeMOODY G2 SUS 2000 NW MFL BK/BK. Lamp brand. Body made of black aluminium extrusion, with MFL polycarbonate reflector, and black trim ring, with high visual comfort (UGR <19). Model for COB LEDs with neutral white colour temperature and built-in electronic equipment. With IP20 degree of protection. Insulation class I.



Finish: Matte black RAL 9011

Weight: 640 g

Installation: Suspended

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 1.592 lm
 ⁰K :
 4000

 Plum:
 20,5W
 CRI :
 80

 Efficacy:
 77,7 lm/w
 MacAdam:
 3

**Type:** COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 18W

## Light output tolerance +/- 10%

















## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU




















## **MOODY**










## **PHOTOMETRIC DATA:**

MO2SU20MF840NBB  $\eta$  = 100% Imax = 3143 cd/klm UTE: CIE: 99 100 100 100 100







Data according to regulations 2019/2020/EU and 2019/2015/EU