#### **Product datasheet**

#### **MOODY**

# Worktitude for light


### MO2SU20MF840NBW



### MOODY G2 SUS 2000 NW MFL BK/WH.

### Description:

Suspended downlight modeMOODY G2 SUS 2000 NW MFL BK/WH. Lamp brand. Body made of white aluminium extrusion, with MFL polycarbonate reflector, and black trim ring, with high visual comfort (UGR <19). Model for COB LEDs with neutral white colour temperature and built-in electronic equipment. With IP20 degree of protection. Insulation class I.



Finish: Matte white RAL 9010

Weight: 640 g

Installation: Suspended

### **TECHNICAL SPECIFICATIONS:**

 Light output:
 1.592 lm
 ⁰K :
 4000

 Plum:
 20,5W
 CRI :
 80

 Efficacy:
 77,7 lm/w
 MacAdam:
 3

**Type:** COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 18W

## Light output tolerance +/- 10%

















# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU


















### **MOODY**










### **PHOTOMETRIC DATA:**

$$\label{eq:mo2SU20MF840NBW} \begin{split} \eta &= 100\% \\ \text{Imax} &= 3143 \text{ cd/klm} \\ \text{UTE:} \\ \text{CIE: } 99 \ 100 \ 100 \ 100 \ 100 \end{split}$$







Data according to regulations 2019/2020/EU and 2019/2015/EU