Product datasheet

PUCK



MP1201505-70-30



PUCK XT ASYM 3000K 1.5W

Description:

Puck XT LED luminaire by WILA 1.5W suitable for round handrail, 38-100mm Diameter, with one-sided asymmetrical light distribution, warm white (3000K). D=18mm with 1mm thread, made of stainless steel, with polycarbonate lens, IP66, curved face, wall thickness >1.5mm.



Finish: Stainless steel AISI 316

Dimensions: Ø 16 mm x 15 mm **Weight:** 16 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 159 lm **°K**: 3000

CRI: 80

Efficacy: 106 lm/w MacAdam: 3

LED Lifetime: 50.000 L90 B10 (Ta=25°C) **Power Supply:** 500mA

Power: 1,5W **Gear:** Without gear (requires external gear)

Light output tolerance +/- 10%










Web www.lamp.es


PUCK










PHOTOMETRIC DATA:









Product datasheet

PUCK



ACCESORIES:

Assembly



Product code:

MP-002



Product code:

MP-003



GEL CONNECTORS (2 REQUIRED PER PUCK)



Product code:

MP-004

Description:

LOCTITE 243 10ML BOTTLE

PUCK CRIMP PLIERS/TOOL



Product code:

MP-011

Description:

Description:

PUCK XT ASYM INSERTION TOOL

ACCESORIES:

Adjustment and control



Product code:

MPPSU001D-SELV

Description:

PUCK XT DRV DALI-2 4-18 Pucks 500mA SWI



Product code:

MPXTPSU002A500-D

PUCK XT DRV DALI 19-50 Pucks 500mA PROGR