Product datasheet

PUCK



MP1201505-70-40



PUCK XT CURVED 4000K ASYM 1.5W

Description:

Puck XT LED luminaire by WILA 1.5W suitable for round handrail, 38-100mm Diameter, with one-sided asymmetrical light distribution, neutral white (4000K). D=18mm with 1mm thread, made of stainless steel, with polycarbonate lens, IP66, curved face, wall thickness >1.5mm.



Finish: Stainless steel AISI 316

Dimensions: Ø 18 mm x 15 mm **Weight:** 16 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 169 lm **°K**: 4000

CRI: 80

Efficacy: 113 lm/w MacAdam: 3

LED Lifetime: 50.000 L90 B10 (Ta=25°C) **Power Supply:** 500mA

Power: 1,5W **Gear:** Without gear (requires external gear)

Light output tolerance +/- 10%















PUCK








PUCK XT CURVED 4000K ASYM 1.5W

PHOTOMETRIC DATA:









Product datasheet

PUCK



ACCESORIES:

Assembly



Product code:

MP-002



PUCK CRIMP PLIERS/TOOL



Product code:

MP-003



GEL CONNECTORS (2 REQUIRED PER PUCK)



Product code:

Description:

MP-004 LOCTITE 243 10ML BOTTLE



Product code:

MP-011

Description:

PUCK XT ASYM INSERTION TOOL

ACCESORIES:

Adjustment and control



Product code: MPPSU001D-SELV

Description:

PUCK XT DRV DALI-2 4-18 Pucks 500mA



Product code:

Description:

MPXTPSU002A500-D PU0

PUCK XT DRV DALI 19-50 Pucks 500mA

Data according to regulations 2019/2020/EU and 2019/2015/EU