#### **Product datasheet**

### **OWL**

# **LAMP**Worktitude for light


### OW1051ST740NG



### OWL CL.I 4800 NW GR.

### Description:

Street luminaire model OWL CL.I 4800 NW GR., LAMP brand. Body manufactured of texturised grey lacquered aluminum injection, with serigraphed tempered flat glass. Passive dissipation through the body. Model for HIPOWER LED, neutral white color temperature and control gear included. With street optics. IP66, IK07 protection rating. Insulation class I. Its ball joint allows swiveling the light between 10° and -10°.



Finish: Texturised grey

Weight: 6.266 g

Maximum surface exposed to wind: 0.19 M2

Installation: Integrated in light-pole

### **TECHNICAL SPECIFICATIONS:**

 Light output:
 3.871 lm
 °K:
 4000

 Plum:
 36W
 CRI:
 70

 Efficacy:
 107,5 lm/w
 MacAdam:
 4

Type: HI POWER OSRAM Power Supply: 220-240V 50/60Hz

LED Lifetime: 100.000 L90 B10 Gear: Electronic

Power: 33W





















## **CUSTOM MADE OPTIONS:**





























## **OWL**









### **PHOTOMETRIC DATA:**







H (m)	D (m)	Emax	Emed
1	5,39	1507	162
2	10,78	377	40
3	16,17	167	18
4	21,56	94	10

## **Product datasheet**

## **OWL**



ACCESORIES:

Support



Product code:

Description:

OWAR1000G OWL ACC.WALL ARM 1M GR.