Product datasheet

OWL

LAMPWorktitude for light

OW1051ST830NG



OWL CL.I 4800 8WW GR.

Description:


Street luminaire model OWL CL.I 4800, LAMP brand. Body manufactured of texturised grey lacquered aluminum injection, with serigraphed tempered flat glass. Passive dissipation through the body. Model for HI-POWER LED, 3000K color temperature, CRI80 and control gear included and control gear included. With street optics. IP66, IK07 protection rating. Insulation class I. Its ball joint allows swiveling the light between 10° and -10°. Lifetime: 100.000 L90 B10

Finish: Texturised grey

Weight: 6.266 g

Maximum surface exposed to wind: 0.19 M2

Installation: Integrated in light-pole



TECHNICAL SPECIFICATIONS:

 Light output:
 3.871 lm
 °K:
 3000

 Plum:
 37,6W
 CRI:
 80

 Efficacy:
 103 lm/w
 MacAdam:
 4

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 100.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 32W

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU


















OWL










PHOTOMETRIC DATA:

H (m)	D (m)	Emax	Emed
1	4,75	1599	207
2	9,51	400	52
3	14,26	178	23
4	19,01	100	13







Product datasheet

OWL



ACCESORIES:

Support



Product code:

Description:

OWAR1000G OWL ACC.WALL ARM 1M GR.