#### **Product datasheet**

### **OWL**

### OW1051ST840NG



### OWL CL.I 4800 8NW GR.

### Description:


Street luminaire model OWL CL.I 4800, LAMP brand. Body manufactured of texturised grey lacquered aluminum injection, with serigraphed tempered flat glass. Passive dissipation through the body. Model for HI-POWER LED, 4000K color temperature, CRI80 and control gear included and control gear included. With street optics. IP66, IK07 protection rating. Insulation class I. Its ball joint allows swiveling the light between 10° and -10°. Lifetime: 100.000 L90 B10

Finish: Texturised grey

Weight: 6.266 g

Maximum surface exposed to wind: 0.19 M2

Installation: Integrated in light-pole



### **TECHNICAL SPECIFICATIONS:**

Light output: 3.871 lm °K: 4000 Plum: 36W CRI: 80 Efficacy: 107,5 lm/w 4 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 100.000 L90 B10 (Ta=25°C) Gear: Electronic

32W Power:

## Light output tolerance +/- 10%

























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU



















# **OWL**





OWL CL.I 4800 8NW GR.




### **PHOTOMETRIC DATA:**

H (m)	D (m)	Emax	Emed
1	4,75	1599	207
2	9,51	400	52
3	14,26	178	23
4	19,01	100	13







# **Product datasheet**

# **OWL**



ACCESORIES:

Support



Product code:

Description:

OWAR1000G OWL ACC.WALL ARM 1M GR.