

## OW1091ST830NG



## OWL CL.I 8500 8WW GR.

## Description:


Street luminaire model OWL CL. I 8500, LAMP brand. Body manufactured of texturised grey lacquered aluminum injection, with serigraphed tempered flat glass. Passive dissipation through the body. Model for HI-POWER LED, 3000K color temperature, CRI80 and control gear included and control gear included. With street optics. IP66, IK07 protection rating. Insulation class I. Its ball joint allows swiveling the light between 10° and -10°. Lifetime: 100.000 L90 B10. BUG Rate: B2 U0 G2, ULOR 0%.

**Finish:** Texturised grey

**Weight:** 6.266 g

**Maximum surface exposed to wind:** 0.19 M2

**Installation:** Integrated in light-pole



## TECHNICAL SPECIFICATIONS:

<b>Light output:</b>	7.789 lm	<b>°K :</b>	3000
<b>Plum:</b>	68W	<b>CRI :</b>	80
<b>Efficacy:</b>	114,5 lm/w	<b>MacAdam:</b>	4
<b>Type:</b>	HIGH POWER LED	<b>Power Supply:</b>	220-240V 50/60Hz
<b>LED Lifetime:</b>	100.000 L90 B10 (Ta=25°C)	<b>Gear:</b>	Electronic
<b>Power:</b>	62W		

*Light output tolerance +/- 10%*





## CUSTOM MADE OPTIONS:



PHOTOMETRIC DATA :

H (m)	D (m)	E <sub>max</sub>	E <sub>med</sub>
1	5,41	3031	324
2	10,81	758	81
3	16,22	337	36
4	21,63	189	20



OW1091ST830NG

$\eta$  = 101%

I<sub>max</sub> = 856 cd/klm

UTE: 1,00E + 0,00T

CIE: 40 78 98 100 101

---

ACCESORIES :

Support



**Product code:**

OWAR1000G

**Description:**

OWL ACC.WALL ARM 1M GR.