

OW1091ST840NG



OWL CL.I 8500 8NW GR.

Description:


Street luminaire model OWL CL. I 8500, LAMP brand. Body manufactured of texturised grey lacquered aluminum injection, with serigraphed tempered flat glass. Passive dissipation through the body. Model for HI-POWER LED, 4000K color temperature, CRI80 and control gear included and control gear included. With street optics. IP66, IK07 protection rating. Insulation class I. Its ball joint allows swiveling the light between 10° and -10°. Lifetime: 100.000 L90 B10. BUG Rate: B2 U0 G2, ULOR 0%.

Finish: Texturised grey

Weight: 6.530 g

Maximum surface exposed to wind: 0.19 M2

Installation: Integrated in light-pole



TECHNICAL SPECIFICATIONS:

Light output:	7.789 lm	°K :	4000
Plum:	68W	CRI :	80
Efficacy:	114,5 lm/w	MacAdam:	4
Type:	HIGH POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	100.000 L90 B10 (Ta=25°C)	Gear:	Electronic
Power:	62W		

Light output tolerance +/- 10%





CUSTOM MADE OPTIONS:



PHOTOMETRIC DATA :

H (m)	D (m)	E _{max}	E _{med}
1	5,41	3031	324
2	10,81	758	81
3	16,22	337	36
4	21,63	189	20



OW1091ST840NG

$\eta = 101\%$

$I_{max} = 856 \text{ cd/klm}$

UTE: 1,00E + 0,00T

CIE: 40 78 98 100 101

ACCESORIES :

Support



Product code:

OWAR1000G

Description:

OWL ACC.WALL ARM 1M GR.