#### **Product datasheet**

#### **OWL**

# **LAMP**Worktitude for light


#### OW1092ST740NG



#### OWL CL.II 8500 NW GR.

#### Description:

Street luminaire model OWL CL.II 8500 NW GR., LAMP brand. Body manufactured of texturised grey lacquered aluminum injection, with serigraphed tempered flat glass. Passive dissipation through the body. Model for HI-POWER LED, neutral white color temperatur e and control gear included. With street optics. IP66, IK07 protection rating. Insulation class II. Its ball joint allows swiveling the light between 10° and -10°.



Finish: Texturised grey

Weight: 6.580 g

Maximum surface exposed to wind: 0.19 M2

Installation: Integrated in light-pole

#### **TECHNICAL SPECIFICATIONS:**

 Light output:
 7.789 lm
 °K:
 4000

 Plum:
 64W
 CRI:
 70

 Efficacy:
 121,7 lm/w
 MacAdam:
 4

Type: HI POWER OSRAM Power Supply: 198-265V 50/60Hz

LED Lifetime: 100.000 L90 B10 Gear:

Power: 59W























# **CUSTOM MADE OPTIONS:**
























Electronic




## **OWL**








#### **PHOTOMETRIC DATA:**





alpha = 139,3°	H (m)	D (m)	Emax	Emed
	1	5,39	3032	325
	2	10,78	758	81
	3	16,17	337	36
	4	21,56	190	20

# **Product datasheet**

## **OWL**



ACCESORIES:

Support



Product code:

Description:

OWAR1000G OWL ACC.WALL ARM 1M GR.