Product datasheet

OWL

LAMPWorktitude for light


OW1151ST740NG



OWL CL.I 14500 NW GR.

Description:

Street luminaire model OWL CL.I 14500 NW GR., LAMP brand. Body manufactured of texturised grey lacquered aluminum injection, with serigraphed tempered flat glass. Passive dissipation through the body. Model for HIPOWER LED, neutral white color temperature and control gear included. With street optics. IP66, IK07 protection rating. Insulation class I. Its ball joint allows swiveling the light between 10° and -10°.



Finish: Texturised grey

Weight: 6.502 g

Installation: Integrated in light-pole

TECHNICAL SPECIFICATIONS:

 Light output:
 13.277 lm
 °K:
 4000

 Plum:
 110W
 CRI:
 70

 Efficacy:
 120,7 lm/w
 MacAdam:
 4

Type: HI POWER OSRAM Power Supply: 220-240V 50/60Hz

LED Lifetime: 100.000 L90 B10 Gear: Electronic

Power: 103W





















CUSTOM MADE OPTIONS:


























OWL




OWL CL.I 14500 NW GR.



PHOTOMETRIC DATA:





alpha = 139,3°	H (m)	D (m)	Emax	Emed
	1	5,39	5168	554
	2	10,78	1292	139
	3	16,17	574	62
	4	21,56	323	35

Product datasheet

OWL



ACCESORIES:

Support



Product code:

Description:

OWAR1000G OWL ACC.WALL ARM 1M GR.