Product datasheet

PLAT


PL306035OP4030DW



PLAT G3 600X600 3400 WW OPAL IP40 DA WH

Description:

Recessed or suspended luminaire model PLAT G3, LAMP brand. Made of matt white steel with opal polycarbonate diffuser. Model with MID-POWER LED, 3000K colour temperature and CRI 80. Control DALI gear included. With a protection rating of IP40 (non-recessed part) and IP20 (recessed part), IK06. Insulation class II. Photobiological safety group 0. Lifetime: 70.000h L80 B10.



Finish: Matte Traffic white RAL 9016

596 x 596 x 14 mm Dimensions: Weight: 3.900 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.607 Im °K: 3000 Plum: 31W CRI: 80 Efficacy: 116,4 lm/w 3 MacAdam:

Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

28W Power:

Light output tolerance +/- 10%

































Data according to regulations 2019/2020/EU and 2019/2015/EU

PLAT







PLAT G3 600X600 3400 WW OPAL IP40 DA WH

PHOTOMETRIC DATA:

PL306035OP4030NW η = 100% lmax = 345 cd/klm UTE: 1,00E

CIE: 46 78 96 100 100





alpha = 114,1°	H (m)	D (m)	Emax	Emed
	1	3,08	1242	360
	2	6,17	311	90
	3	9,25	138	40
	4	12,34	78	23

Product datasheet

PLAT



ACCESORIES:

Assembly



Product code: Description:

PLREFR060 PLAT ACC. FRAME REC 600X600MM WH.



Product code: PLSFFR060 Description:

PLAT ACC. FRAME SUR 600X600MM WH.

ACCESORIES:

Suspension



Product code:

Description:

PLSUWI1500 PLAT G3 ACC. SUSP KIT

PLAT





