Product datasheet

PLAT


PL306035OP40840NW



PLAT G3 600X600 3600 840 OPAL IP40 WH

Description:

Recessed or suspended luminaire model PLAT G3, LAMP brand. Made of matt white steel with opal polycarbonate diffuser. Model with MID-POWER LED, 4000K colour temperature and CRI 80. Control gear included. With a protection rating of IP40 (non-recessed part) and IP20 (recessed part), IK06. Insulation class II. Photobiological safety group 0. Lifetime: 70.000h L80 B10



Finish: Matte Traffic white RAL 9016

596 x 596 x 14 mm Dimensions: Weight: 3.900 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.819 lm °K: 4000 Plum: 31W CRI: 80 Efficacy: 123,2 lm/w 3 MacAdam:

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear: Electronic

28W Power:

Light output tolerance +/- 10%





































Data according to regulations 2019/2020/EU and 2019/2015/EU













PLAT









PHOTOMETRIC DATA:

PL306035OP40840NW η = 100% Imax = 349 cd/klm UTE: 1,00E + 0,01T CIE: 47 78 96 99 100





Product datasheet

PLAT



ACCESORIES:

Assembly



Product code: Description:

PLREFR060 PLAT ACC. FRAME REC 600X600MM WH.



Product code: PLSFFR060 Description:

PLAT ACC. FRAME SUR 600X600MM WH.

ACCESORIES:

Suspension



Product code:

Description:

PLSUWI1500 PLAT G3 ACC. SUSP KIT