Product datasheet

PLAT




PL306035OP408TWDW



PLAT G3 600X600 3500 8TW OPAL IP40 DA WH

Description:

Recessed or suspended luminaire model, PLAT G3, LAMP brand. Made of matt white steel with opal polycarbonate diffuser. Model with MID-POWER LED, TW colour temperature and CRI 80. Control gear included. With a protection rating of IP40 (non-recessed part) and IP20 (recessed part), IK06. Insulation class II. Photobiological safety group 0. Lifetime: 70.000h L80 B10



Finish: Matte Traffic white RAL 9016

596 x 596 x 14 mm Dimensions: Weight: 4.300 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 4.495 lm °K: 2700-6500

Plum: 36W CRI: 80 Efficacy: 124,9 lm/w 3 MacAdam:

Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L80 B50 (Ta=25°C) Gear: Adjustable DALI DT8

31W Power:

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:











Data according to regulations 2019/2020/EU and 2019/2015/EU

PLAT






PLAT G3 600X600 3500 8TW OPAL IP40 DA WH

PHOTOMETRIC DATA:

PL306035OP408TWDW $\eta = 100\%$ lmax = 341 cd/klmUTE: 1,00E

CIE: 46 78 96 100 100





alpha = 114,8°	H (m)	D (m)	Emax	Emed
	1	3,12	1530	439
	2	6,25	383	110
	3	9,37	170	49
	4	12,50	96	27

Product datasheet

PLAT



ACCESORIES:

Assembly



Product code: Description:

PLREFR060 PLAT ACC. FRAME REC 600X600MM WH.



Product code: PLSFFR060 Description:

PLAT ACC. FRAME SUR 600X600MM WH.

ACCESORIES:

Suspension



Product code:

Description:

PLSUWI1500 PLAT G3 ACC. SUSP KIT