PLAT


PL306035OP5440DW



PLAT G3 600X600 3600 NW OPAL IP54 DA WH

Description:

Recessed or suspended luminaire model PLAT G3, LAMP brand. Made of matt white steel with opal polycarbonate diffuser. Model with MID-POWER LED, 4000K colour temperature and CRI 80. Control DALI gear included. With a protection rating of IP54 (non-recessed part) and IP20 (recessed part), IK06. Insulation class II. Photobiological safety group 0. Lifetime: 70.000h L80 B10.



Finish:Matte Traffic white RAL 9016Dimensions:596 x 596 x 14 mm

Weight: 3.900 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	3.819 lm	°К:	4000	
Plum:	31W	CRI :	80	
Efficacy:	123,2 lm/w	MacAdam:	3	
Туре:	MID POWER LED	Power Supply:	220-240V 50/60Hz	
LED Lifetime:	70.000 L80 B10 (Ta=25ºC)	Gear:	Adjustable DALI	
Power:	28W			

Light output tolerance +/- 10%



Worktitude for light

PLAT

PL306035OP5440DW

PLAT G3 600X600 3600 NW OPAL IP54 DA WH



PL306035OP5440NW	180°	alpha = 114,1°	H (m)	D (m)	Emax	Emed
η = 100%			1	3,08	1315	381
lmax = 345 cd/klm						
UTE: 1,00E	90° 90°		2	6,17	329	95
CIE: 46 78 96 100 100						
			3	9,25	146	42
	0°		4	12,34	82	24



PLAT



ACCESORIES :

Assembly



Product code: PLREFR060 Description: PLAT ACC. FRAME REC 600X600MM WH.



Product code: PLSFFR060 Description: PLAT ACC. FRAME SUR 600X600MM WH.

ACCESORIES : Suspension



Product code: PLSUWI1500 Description: PLAT G3 ACC. SUSP KIT







LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es